

TEKON
WIRELESS SENSORS TECHNOLOGY

Turn-key wireless solution for
lightweight monitoring applications
of temperature, humidity,
CO₂, barometric pressure
and air-quality



DUOS

WIRELESS SMART SENSORS

APPLICATIONS



Offices PORTUGAL

Temperature, humidity, CO2 and barometric pressure are some of the critical variables that need to be measured in order to keep the environment in safe patterns. Wireless monitoring with alarms and user notifications to ventilate the area allows to keep all the values in a healthy standard.



Pharmaceutical UNITED KINGDOM

DUOS wireless smart sensors are being used to monitor and report temperature and humidity values in a pharmaceutical application with restricted product and workplace quality control.



Blood Bank LATVIA

DUOS wireless sensors were integrated into a blood bank, to monitor temperature, humidity and digital input state to ensure the security of blood and derivatives assets. All data was available in the local automation and stored in a cloud service.




Museums PORTUGAL

Our temperature and humidity monitoring solutions are helping to preserve our history. Tekon Electronics implemented wireless solutions in the museum's exhibition and storage rooms, in order to minimize the interference of these variables in the preservation process. The solution was backed with our Tekon IoT Platform to establish a real-time monitoring system to ensure a timely intervention in the temperature control of these spaces.

Smart Sensors

Easy-to-set and intuitive wireless monitoring solution developed for fast commissioning and quick access to IoT data.





Transmitters

Smart IoT solutions with external sensors for a reliable wireless monitoring of environmental variables.

DUOS Hygrotemp



Temperature and Humidity

- -40°C to 60°C Temperature range
- 0% to 100% Humidity range
- Calibration options
- IP67 protection
- Integration with Tekon IoT Platform
- External sensor up to 2m

DUOS Multitemp



Temperature

- Up to 5 measuring points
- -40°C to 90°C External Temperature range
- -40°C to 60°C Internal Temperature range
- Calibration options
- IP67 protection
- Integration with Tekon IoT Platform




temperature



humidity



CO₂



barometric pressure



digital input



millivolts



ohms

DUOS Temp



Temperature

- -40°C to 60°C Temperature range
- Multiple probe options (*)
- Calibration options
- IP67 protection
- Integration with Tekon IoT Platform

(*) Probe with 125°C range available

DUOS Di+Temp



Temperature and Digital Input

- -40°C to 60°C Temperature range
- Dry contact digital input
- Calibration options
- IP67 protection
- Integration with Tekon IoT Platform

DUOS uTemp



Universal Temperature and Digital Input

- RTD, Thermocouples, mv and ohm sensors
- -40°C to 60°C Internal Temperature range
- Calibration options
- IP67 protection
- Integration with Tekon IoT Platform



DUOS inTemp



Temperature and Digital Input

- -40°C to 60°C Temperature range
- Built-in sensor
- Dry contact digital input
- Calibration options
- IP65 protection
- Integration with Tekon IoT Platform

inSensors

Smart IoT solutions with built-in sensors for a reliable wireless monitoring of environmental variables.

DUOS InHygrotemp



Temperature Humidity and Digital Input

- -40°C to 60°C Temperature range
- 0% to 100% Humidity range
- Built-in sensor
- Dry contact digital input
- Calibration options
- IP65 protection
- Integration with Tekon IoT Platform

DUOS InAir



Temperature, CO2, Average CO2, Humidity, Barometric Pressure and Digital Input

- -40°C to 60°C Temperature range
- 0 to 5000 ppm CO2 range
- 0 to 100% Humidity range
- 700mbar to 1100mbar Barometric Pressure
- Dry contact digital input
- Calibration options
- IP65 protection
- Integration with Tekon IoT Platform

Duos InCO2



Temperature, CO2, Average CO2, Barometric Pressure and Digital Input

- -40°C to 60°C Temperature range
- 0 to 5000 ppm CO2 range
- 700mbar to 1100mbar Barometric Pressure
- Dry contact digital input
- Calibration options
- IP65 protection
- Integration with Tekon IoT Platform

MODELS

	TEMPERATURE		DIGITAL INPUT	CO ₂		HUMIDITY		BAROM. PRESSURE	MV	Ω
	EXTERNAL	INTERNAL		EXTERNAL	INTERNAL	EXTERNAL	INTERNAL			
TEMP	●	●								
HYGROTEMP	●	●		●		●				
DI+TEMP	●	●	●							
MULTITEMP	●	●								
UTEMP	●	●	●						●	●
INTEMP		●	●							
INHYGROTEMP		●	●				●			
INCO ₂		●	●		●			●		
INAIR		●	●		●		●	●		

Gateways

Smart endpoints of DUOS wireless solutions for Modbus data transmission or TCP/IP communication.



DUOS IoT Gateway

- Ethernet TCP/IP communication
- Modbus TCP/IP communication
- Integration with Tekon IoT Platform
- Scalable network up to 55 smart sensors
- Up to 13 repeaters in series
- IP40 protection
- AES-128 bits data encryption

DUOS Gateway

- Modbus RTU via RS485
- Scalable network up to 55 smart sensors
- Up to 13 repeaters in series
- IP40 protection
- AES-128 bits data encryption

Repeater

Wireless signal repeater for network redundancy that ensures an efficient communication in any application.



DUOS Repeater

- Compatible with all smart sensors and gateways
- Up to 13 repeaters in series
- IP40 protection
- AES-128 bits data encryption

uGateway


Smart Industrial IoT Gateway

UNIVERSAL IoT GATEWAY

IIoT MADE SIMPLE!



COLLECT, RECORD, SEND AND ANALYZE




TECHNICAL SPECIFICATIONS

- Processor :** Arm Quad Core Cortex-A72 64-bit SoC
- I/O:** WiFi LAN: 2.4 GHz
Radio wireless interface 868/915MHz (used by Tekon transmitters)
Mobile: 3G/4G cellular Modem (optional)
Serial: RS-485
Ethernet: 100/1000 Mbps
- Memory:** 16 GB eMMC flash
- Protocols:** Modbus RTU, Modbus TCP/IP, MQTT

User interface

Through the browser-based user interface, the transmitted data offers users the highest level of transparency. Accessing product data during development enables rapid planning and reduces timelines. Processes become measurable, enhancing production flexibility.



Data analysis

Real-time alarms and notifications

Device management

IoT platform connectivity

Open solution for third-party systems



TEKON ELECTRONICS
a brand of Bresimar Automação S.A.

Avenida Europa, 460
Quinta do Simão - Esgueira
3800-230 Aveiro
PORTUGAL

P.: +351 234 303 320
E.: sales@tekonelectronics.com

Authorized Local Distributor

Tekon Electronics is a trademark of Bresimar Automação S.A.

The information provided in this catalogue, contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.

Cofinanciado por:

