



PLUS WRP001 INSTALLATION GUIDE

IG_PLUS_WRP001_E02A

PLUS WRP001 WIRELESS REPEATER INSTALLATION GUIDE

Table of contents

step 01	WRP001 PLUS WIRELESS REPEATER CONFIGURATION Pages 3 to 10
-------------------	---

step 02	SITE SURVEY MODE Pages 11 to 12
-------------------	---

step
01

WRP001 PLUS WIRELESS REPEATER CONFIGURATION

step

01

CONNECT AND CONFIGURE THE PLUS WIRELESS REPEATER


01

Loosen the 4 screws of the case and open it.



02

Connect a micro USB cable to the computer and then to *WRP001 PLUS Wireless Repeater*.



03


Open *Tekon Configurator Software*




CONNECT AND CONFIGURE THE PLUS WIRELESS REPEATER

04 Open the WRP001 PLUS Wireless Repeater device page.
You can enter the device's page in the following ways:

1st option: Click on **"SMART TRANSMITTERS"** in the left menu and then click on the device.



2nd option: Type the name of the device in the **"Search Device"** field on the home page and select.




step

01

CONNECT AND CONFIGURE THE PLUS WIRELESS REPEATER

05

Load the “Port COM” corresponding to the WRP001 PLUS Wireless Repeater.




NOTE:

If the USB cable has already been connected before opening the device page, “Port COM” will appear in the list, otherwise you need to click on the “🔌” button.

06

Select corresponding *Port COM*².





² You can check device’s serial port name in “Device Manager” on Microsoft® Windows® operating system.

CONNECT AND CONFIGURE THE PLUS WIRELESS REPEATER step
01

07

Click on  to enter in *Configuration Mode*




step

01

CONNECT AND CONFIGURE THE PLUS WIRELESS REPEATER

08

The software will connect to the device.




NOTE:

If the software is unable to connect to the device, the **Unexpected Error** status is displayed. If it hasn't connected, go back to the previous steps and check the port COM.


09

When the software connects to the device, the "Connected" message will be displayed.




CONNECT AND CONFIGURE THE PLUS WIRELESS REPEATER

10 Configure the “*Wireless Network ID*” and “*Wireless Channel*” previously obtained from the Gateway. Click on the “*WRITE DEVICE*” button to update the transmitter settings. .



11 Wait for the software to write the new setting to the device. Wait for the status  change to  .



If not, the following symbol will appear (), try again and check that the device is connected correctly.



step

01

CONNECT AND CONFIGURE THE PLUS WIRELESS REPEATER

12

Click  to exit the configuration and return to normal operating mode.



step
02

SITE SURVEY MODE

step
02 | SITE SURVEY MODE


Site survey mode is a tool that allows a quick wireless signal strength evaluation at the site of installation. It doesn't require additional equipment or software.

This feature is available in all the transmitters and repeater from PLUS Product Family.

01

Press and hold Mode () button until Status LEDs are permanently on and Mode LEDs flash.

RSSI LEDs indicate the signal strength.



02

Press and hold Mode () button until RSSI LEDs switch off and device resumes normal operation mode.

TEKON ELECTRONICS

a brand of Bresimar Automação S.A.

Avenida Europa, 460
Quinta do Simão
3800-230 Aveiro
PORTUGAL

Sales

P.: +351 234 303 320
M.: +351 933 033 250
E.: sales@tekonelectronics.com

Technical Support

E.: support@tekonelectronics.com

